

**Legend**

	Consumer Unit
	Provisions For Light Switch
	Ceiling Mounted P.I.R Light Sensor
	CAT2 Twin Light
	2kW Convector Heater c/w 24/7 Timer
	Dbi. Skt. @300mm Up F.F.F.L
	Dbi. Skt. @1100mm Up F.F.F.L
	2kW, 10Ltr. Undersink Water Heater
	High & Low Level Small Plastic Vents

**\*\*PLEASE NOTE\*\***

3'x3', WHITE, UPVC FRAMED, DOUBLE GLAZED, TILT & TURN WINDOWS c/w KIRNCROFT SHUTTERS.  
 'KIRNCROFT' PERSONNEL DOORS c/w DOOR CLOSERS.  
 STAINLESS STEEL, INSET SINK, c/w NON CONCUSSIVE TAPS.  
 1M BASE UNIT BELOW c/w UNDERSINK WATER HEATER. FULL WIDTH WORKTOP c/w D/SOCKETS ABOVE & BELOW.  
 2kW CONVECTOR HEATER c/w 24/7 TIMERS.  
 P.I.R CEILING MOUNTED LIGHT SENSORS. FIT PROVISIONS FOR LIGHT SWITCHES.

**Lining Details**

WALLS	GREY, ECO 6mm & 50mm INSULATION
CEILING	WHITE, ECO 6mm & 50mm INSULATION
TRIMS	WHITE PLASTIC
FLOOR	VINYL FLOORING OVER 15mm PLYWOOD

PROFILED	
FLATSIDED	
A	Details
Rev.	
Drn.	JT
Approved By:	
Name:	
Signature:	
Date:	28/08/14

FLAT SIDED CONSTRUCTION

